

TECHNICAL DATA SHEET

# Gemalto Document Reader AT10K



## Product Use

Inspect, authenticate or capture data from electronic travel and identity documents quickly and reliably with the Gemalto Document Reader AT10K.

Designed for use in demanding border management scenarios, it also serves banking, hospitality, travel and any other industries where you need accurate and reliable document and ID verification and reading.

The design of the Gemalto AT10K is based on detailed and exhaustive analysis of field experience and numerous deployed projects. With a new "landing lights" LED feedback arrangement and document hold down clip it naturally encourages the correct placement and use of the reader, regardless if the user is left or right handed, maximising first time read rate for faster customer processing.

Gemalto has created a new stylish look that will fit into the décor of the most upmarket customer facing service desks.

## Functions include:

- > Optional support for biometrically enabled travel documents and driving licenses containing contactless integrated circuit chips (eIDs, eDLs and ePassports)
- > Optical document authentication and verification in border management, police, transportation, banking and other commercial markets using additional software package
- > Accurate, true-color images, with anti-glare technology to reduce document laminate reflections and ambient light interference therefore improving image quality
- > A new progress bar with Tick / Cross indicators make reading a document intuitive, helping to direct the user during a read and visually show the result of the read
- > Removable hood for easy document and mobile device placement, especially when using gloves
- > New design of document spine hold down clip, holds down new books and works on multiple, stapled books
- > Reads 1D and 2D barcodes from paper and mobile devices

# Gemalto Document Reader AT10K



## FEATURES

- > Reads and images multiple types of documents in Visible, Infra-red and Ultra-violet light using 24-bit color and true-color image matching technology
- > Reads documents and barcodes placed at any rotation on the glass and presents images correct way up based on features in document
- > Anti-glare technology eliminates image artifacts due to laminate or OVDs
- > OCR data capture of the Machine Readable Zone (MRZ)
- > Auto-triggering of document capture – presence of document is automatically detected
- > Hoodless operation in many environments (kiosk mode)
- > User removable hood and optional document spine hold down clip provide flexibility for the user to operate in their preferred style
- > Internally sealed optical chamber prevent dust ingress
- > Low scratch, low-iron glass with oleophobic coating for low maintenance & easy cleaning
- > Corning® Gorilla® Glass (optional) to improve durability
- > Powered from USB or external power supply
- > Complete access to OCR data and images captured via Software Development Kit (SDK)
- > Access to images as BMP, PNG or JPEG format
- > Windows® 7, Windows® 8.1, Windows® 10, macOS and Linux® compatible<sup>1</sup>
- > USB 2.0 high speed host port, USB 3.0 compatible
- > Integrated USB 2.0 Hub – 2 ports for external peripherals

## Comprehensive Software Features

- > Uses the same API interface as other Gemalto document readers using Gemalto Document Reader SDK
- > Flexible software interface allows host application to select which illumination sources to use, image type, image compression, photo extraction, reflection or ambient light elimination, color enhancement, which data groups to read, etc.
- > Simple high level API for quick program development or detailed low level API for fine control of all reader functions. SDK provides full configuration API
- > Contactless IC reading for ePassports (LDS 1.7 & 1.8) including basic access control (BAC), passive/active authentication (PA/AA), Chip Authentication (CA), Terminal Authentication (TA), extended access control (EAC v1/v2), supplementary access control (SAC) and PACE-CAM are supported. The SDK provides writing capability using APDUs
- > Contactless IC reading for eDL & iDL (electronic driving licenses) up to DG14 including basic access control (BAP v1), Password Authenticated Connection Establishment (PACE), passive/active authentication (PA/AA), Chip Authentication (CA), Terminal Authentication (TA), supplementary access control (SAC) and extended access control (EAC v1) are supported
- > Full SDK including DLLs, code examples, utilities and demonstration programs. Can be used with Visual C++®, Java® and Microsoft® .NET Framework for Visual Basic® .NET and Visual C#®

## Reading Capability

The Gemalto Document Reader AT10K reads the following documents:

- > ICAO compliant documents in near infrared (IR) per ICAO 9303 specification
- > One line Driving Licenses in near infrared (IR) per ISO18013 part 2 specification
- > 1D barcodes (2 of 5 interleaved, 2 of 5 industrial, Code 128, Code 39, EAN-8 and EAN-13)
- > 2D barcodes used on BCBP and other documents (PDF 417, QR Code®, DataMatrix™ and Aztec formats) from paper documents and many mobile devices

## Illumination

The reader illuminates documents in multiple wavelengths:

- > Near IR B900: 880nm, +/-5%
- > White visible: 430-700nm
- > Ultraviolet (UVA): 365nm

<sup>1</sup>An external power supply is required to activate rear panel peripheral USB ports or when working under Linux and macOS

# Gemalto Document Reader AT10K

## Resolution

- > Standard 370 DPI image resolution, 3.1 Megapixel sensor
- > High Resolution 550 DPI option, 10 Megapixel sensor
- > RGB 24 bit color system

## ePassport (RFID) Option

Reads from and writes to contactless chips and eID according to:

- > ISO 14443 (13.56MHz) Type-A and Type-B using a PC/SC interface
- > ePassport support for ICAO 9303 LDS 1.7 & 1.8 and PKI using included SDK
- > iDL & eDL reading and access control for driving licenses to ISO18013 parts 2 & 3 and ISO/CEI TR 19446 using included SDK
- > All standardized rates, up to 848 Kbps, read-out times depend on RFID tag, operating system and amount of data stored in the chip
- > PC/SC interface provides support to other card types such as Mifare™.
- > SDK certified to BSI TR-03105 Parts 5.1 and 5.2

## Identity Document Verification

Additional software can authenticate an identity document which uses optical pattern matching to:

- > Identify documents based on the type and country of origin
- > Match security features captured from a document against a database of trusted security features
- > Check for presence of UV dull paper
- > Verify that areas are blank, devoid of patterns, text or printed matter
- > Check photo in chip against photo on data page

## Firmware Upgrade

- > Upgradeable firmware via USB 2.0 interface
- > Non-volatile configuration and calibration accessed via USB 2.0 interface

## Regulatory

- > FCC Part 15 Class A
- > CB report
- > US & CA NRTL (pending)
- > CE - RED, LVD & EMC
- > EU WEEE, REACH & RoHS Directive

## Environment

- > Humidity: 20 to 95% (R.H. non-condensing)
- > Temperature: -10° to 50° C operating; -20° to 50° C storage
- > IP52 rating for dust ingress protection in the optical chamber (pending)

## Security

- > Slot for Kensington® Security Lock

## Minimum PC Specification

Software must be installed on a customer-supplied PC, some aspects of read speed may be affected by PC specification. The following minimum configuration is recommended:

- > 2 GHz Pentium® 4 CPU (Intel Core 2 Duo recommended)
- > 1 GB DRAM
- > USB 2.0
- > 60 MB of Hard Drive space for software
- > Windows® 7, Windows® 8.1 or Windows® 10 operating systems, 32 or 64 bit
- > Builds for Ubuntu and CentOS LTS, 32 & 64 bit<sup>2</sup>
- > macOS (limited SDK functionality)<sup>2</sup>

## Standard Dimensions

- > Length: 18.7 cm (7.4")
- > Width: 16.0 cm (6.3")
- > Height: 6.5 cm (2.6") without hood, 10.3 cm (4.0") with hood
- > Weight: 1.1 kg (2.4 lbs)

## Status Indicators

The readers provide user feedback via the following status indicators:

- > Red Cross – Indicates a Read Error
- > Green Tick - Indicates a Valid Read
- > Yellow Progress Bar pulsing - Ready to place a new document
- > Yellow Progress Bar incrementing – Performing a read, keep document still on the glass
- > Yellow Progress Bar stopped – Document can be removed from glass

The readers perform a power-up self-test and indicate failure using status LEDs.

<sup>2</sup>An external power supply is required to activate rear panel peripheral USB ports or when working under Linux and macOS

# Gemalto Document Reader AT10K

## Power

Powered from a single USB 2.0 port or via universal input external power supply:

- > Power consumption: 5 volts DC, 500mA (when USB 2.0 powered)

External PSU:

- > Input voltage 100 - 240 VAC plus/minus 10%, Frequency 47 - 63 Hz
- > Detachable IEC320 AC mains power cable

## Optional Add-On Module

- > Contact smartcard to ISO 7816 Class A and AB (T0/T1) (special factory order)

## Service & Maintenance

- > One-year warranty
- > Annual maintenance agreement available

## Contact Gemalto

[www.gemalto.com/Govt](http://www.gemalto.com/Govt)  
Gemalto SA  
6, rue de la Verrerie  
CS 20001  
92197 MEUDON CEDEX

Microsoft, Windows, Windows Vista, Visual C++, Visual C# and Visual Basic are registered trademarks of Microsoft Corporation in the United States and other countries. Java is a registered trademark of Oracle and/or its affiliates. Celeron and Intel are trademarks of Intel Corporation in the U.S. and/or other countries. Data Matrix is a trademark of Robotic Vision Systems, Inc. (RVSII). Ubuntu is a registered trademark of Canonical Ltd. Linux is a registered trademark of Linus Torvalds. Kensington is a registered trademark of ACCO Brands. QR Code is a registered trademark of DENSO WAVE INCORPORATED. MIFARE is a trademark of NXP Semiconductors. macOS is a trademark of Apple Inc., registered in the U.S. and other countries. Corning Gorilla Glass is a trademark of Corning Incorporated.

This document is subject to change without notice.